## 4-ch 1 HDD 4 PoE 4K NVR



Max. 96 Mbps incoming; Max 4 Channel 8MP IPC input; 4-channel 1080P decoding capability;

Support 4K HDMI output; Up to 4 channels for playback; 4 PoE ports; Support P2P, APP Alarm Push; Support Al search;

Al by camera: Face Detection, Intrusion, Tripwire (classification of human/vehicles /non-motor), Object Detection, and SMD

Technical Specifications		
System		
OS	Embedded Linux	
OS Operation Interface	Web/operating in local GUI	
Perimeter Protection by Camera		
Performance	4 channels	
Face Detection by Camera		
Performance	4 channels	
SMD by Camera		
Performance	4 channels	
Video&Audio Input		
Incoming bandwidth	96Mbps	
Output bandwidth	96Mbps	
IPC Input	4CH	
Video&Audio Output		
VGA	1920×1080,1280×1024,1280×720,1024×768	
HDMI	3840×2160,1920×1080,1280×1024,1280×720,1024×768	
Audio Output	1CH,RCA(Line out,2Vp-p,300ohms)	
Audio Encoding		
Audio Compression	G.711A	
Audio Bit Rate	8Kbps(16bit)	
Video&Audio Decoding		
IP channel Resolution	Up to 3840×2160	
Video decoding	H.265 (Main Profile@L5.0 High-tie) /H.264 Up to High Profile@Level5.0)	
Audio decoding	G.711A,G711U,G726	
Synchronous Playback	4CH	
Decoding Ability	4CH 1080P@30FPS/1CH 4K@30FPS	
Preview		
Synchronous Preview	4	
Multi-screen Display	1, 4 views	

## Lite 4K Series | NVR5104H-4P-4K

Playback		
Record Mode	Manual; Schedule (general; MD; alarm; intelligent)	
Al Search	Search by target classification (human, vehicle, non-motor vehicle)	
Backup	USB device	
Playback Function	<ol> <li>Play; pause; stop; fast forward; fast backward; rewind; play by frame</li> <li>Full screen; backup (cut/file); partially enlarge; audio on/off</li> </ol>	
Network		
Network Protocol	HTTP; TCP/IP; IPv4; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; DDNS; FTP; P2P; Auto register	
Mobile Phone Access	Android; iOS	
Interoperability	ONVIF; SDK	
Browser	IE8 or later	
HDD		
SATA	1	
ESATA	0	
Max Capacity	14 TB	
External Interface		
PoE Ports	4	
Network Interface	1 RJ45 100M	
VGA	1	
HDMI	1	
CVBS	0	
USB	2*USB2.0 on Back Panel	
RCA Input	1	
RCA Output	1	
Alarm Input	0	
Alarm Output	0	
RS-232	0	
RS-485	0	
Other Function		
Two-way Talk	Yes	
Alarm Linkage	Record; Snapshot; Buzzer; Log; Preset; Email	
Picture Capture	Support JPEG Capture	
General Parameter		
Front Panel	С	
Packing	410x293x60mm	
Dimensions	Mini 1U 215x235x45mm	
Weight	1.7Kg(No HDD)	
Installation	Desktop Installation	

## Lite 4K Series | NVR5104H-4P-4K

Power Supply	DC 12V 2A	
Working Temperature	-10℃+55℃	
Working Humidity	10%90%	
Consumption	7W(without HDD)	
Certifications		
Certifications	CE/FCC	

## **Dimensions**

